

## Extremely Cost Effective High-Performance Compact Body gives quality



- ✓ Window CE 6.0/ Window Mobile 6.1 for industry standard compatibility
- ✓ Multiple wireless communication options provide connectivity support real time data transmission
- ✓ IP54 level dust and water proof and drop tests to concrete with 6 faces, 6 dimensions
- ✓ High quality QVGA with backlight
- ✓ Embedded flash memory for program upgrade
- ✓ High speed barcode scanning capability in compliance with various standards

## Accessories



## Specifications

|                                |  |   |  |
|--------------------------------|--|---|--|
| <b>CPU</b>                     |  | <b>Operation System</b>   |  |
| Freescale i.MX25 ARM 9 400 MHz |  | Microsoft Windows CE 6.0 / Windows Mobile 6.1<br>English, Traditional & Simplified Chinese versions |  |
| <b>Memory</b>                  |  | <b>Interface</b>  |  |
| Memory - RAM                   | 128MB  | Bluetooth   | Class II, v2.1 with EDR; on-board Antenna  |
| Memory - Flash                 | 128MB  | WLAN  | IEEE 802.11 b/g  |
| <b>Display</b>                 |  | Audio   | Integrated Speaker   |
| Type                           | 3.2" QVGA with backlight   | <b>Environment</b>  |  |
| Resolution                     | 240 x 320 pixels   | Operating temp.   | 0°C to +50°C   |
| Colour                         | Transmissive   | Storage temp.   | -20°C to +70°C (Without battery)   |
| Backlight                      | LED  | Humidity  | 5% to 90% Relative Humidity (No condensation)  |
| Indicator                      | LED, Beep Sound and Vibrator   | Sealing   | IP54   |
| <b>Input</b>                   |  | Drop durability   | Multiple 1.2 m drop to concrete, 6 faces<br>6 times / face in operation temperature range          |
| Keyboard                       | 30 Keys, Numeric<br>3 Trigger Keys<br>4 Colour Function Keys   | <b>Power</b>  |  |
| <b>Scanner</b>                 |  | Operation   | Rechargeable Li-polymer 3.7V 1920mAh (Standard)<br>Rechargeable Li-polymer 3.7V 2880mAh (Extended) |
| Type                           | High Performance Linear Imager   | Backup Memory   | Rechargeable Ni-MH (BUILT-IN)  |
| Scan Rate                      | Dynamic scanning rate up to 500 scans/second   | Backup period   | Minimum 10 mins  |
| Resolution                     | Typical 3mm (Code39, PCS 0.9)  |   |  |
| Distance                       | More than 16 inches on 100% UPC/EAN symbols at 400 lux with Grade A code   |   |  |
| Symbologies                    | Code 39, Code 39 Full ASCII, Code 32, Code 39 Trioptic, Code 128, UCC/EAN-128,<br>Codabar, Code 11, Code 93, Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5,<br>German Postal Code, China Postal Code, IATA, UPC/EAN/JAN, UPC/EAN/JAN |   |  |

Contact Us: If you have further enquiries, please contact us for more information & discussion.

### Million Tech Development Limited



Address: Unit 509, 5/F, Tower II, Cheung Sha Wan Plaza, 833 Cheung Sha Wan Road, Kowloon, Hong Kong  
 General Line: (852) 2788 3306      F a x : (852) 2319 2967      Website: <https://milliontech.com>  
 Sales Enquiry: (852) 2784 2868      Email: [sales@milliontech.com](mailto:sales@milliontech.com)  
 Service Hotline: (852) 2784 2888      Email: [helpdesk@milliontech.com](mailto:helpdesk@milliontech.com)