



# The Wide Web Industrial Compact Design



## **M10e** Series **INDUSTRY VERTICALS**

- Retail
- Healthcare
- Logistics & Transportation

## **APPLICATIONS**

- Compliance Labelling
- Chemical Labelling
- Automotive Labelling
- Paper/Pulp Labelling
- Shipping/Receiving Labelling
- Multiple-Up Labelling
- Lumber Labelling
- Inventory Control Labelling

- *Thermal Transfer Wrinkle-Free Operation*
- *Wide-Web Industrial Printers*
- *Print Technology Replacement and Connectivity*
- *Multilingual Display*
- *High-quality Printing up to 305dpi*
- *Automatic Label Loading via Label Edge Sensor*
- *Fast Print Speed of up to 125mm/sec*
- *Extra-Wide (267 mm) Printing Area for Printing Large Labels or Multiple Labels Per Page*
- *Windows™ Compatible*



# General Specifications

M10e 

PRINTER MODEL		M10eDT	M10eTT
<b>PRINTING SPECIFICATIONS</b>			
Print Method		Direct Thermal	Direct Thermal/Thermal Transfer
Print Resolution		12 dots/mm (305dpi)	
Max. Print Speed		127mm/sec (5ips)	
Max. Print Area		Max (W x P): 266.7 x 420mm (10.5" x 16.55")	
<b>MEDIA SPECIFICATIONS</b>			
Sensor Type		Transmissive sensor for gap. Reflective sensor for I-mark.	
Media		Roll Paper: Max External Diameter 203.2mm (8"), Face-in Fan Fold Paper: Max Folding Height 100mm (3.94") Paper core Internal Diameter 76.2mm (3")	
Media (Thickness)		0.08 to 0.21mm (0.003" to 0.008")	
Media Size	Continuous/Tear OFF/ Cutter	Width: 128 to 297mm (5.04" to 11.70"), inclusive backing paper size 131 to 300 mm (5.16" to 11.82") Pitch: 40 to 297mm (1.58" to 11.70"), inclusive backing paper size 43 to 300 mm (1.69" to 11.82")	
Ribbon Size	Width	145mm (5.71"), 187mm (7.37"), 238mm (9.37"), 273mm (10.76")	
	Length	Max 300m/roll	
	Thickness	7.8 +/- 0.3 μ	
	Winding Direction	Inside wound	
	External Diameter	33.6 +/- 0.4mm (1.32" +/- 0.016")	
	Internal Diameter	25.6 +/- 0.2mm (1" +/- 0.008")	
<b>MEMORY/PROCESSING</b>			
Memory		Standard memory 2MB. Expandable memory 4MB	
CPU		32 bit RISC	
<b>COMMUNICATION INTERFACES</b>			
Plug in Interface Cards		Serial - RS232C Parallel - IEEE1284 Ethernet - 10/100BaseT Wireless 802.11g RS422/485 USB	
<b>FONT/BARCODE SYBLOGIES</b>			
Internal Fonts		XU 5x9 dots, XS 17x17 dots, XM 24x24 dots, XB 48x48 dots, XL 48x48 dots, OCR-A 22x33 dots, OCR-B 30x36 dots	
Internal Raster Fonts		CG Times, CG Triumvirate	
Barcodes	1D Barcode	UPC-A/E, EAN, JAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, Inter-leaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, NW-7, MSI, Postnet, Bookland	
	2D Barcode	QRCode, PDF 417, MaxiCode, Data Matrix	
	Character Rotation	0°, 90°, 180°, 270° rotation	
<b>OPERATING &amp; ENVIRONMENTAL</b>			
Power Consumption		Current AC 100-120 / 200-240 V Peak 560VA 560W (Standby 50VA 40W)	
Environment		Usage Environment: 5 to 40°C / 30 to 80% (with no condensation) Storage Environment: -5 to 60°C / 30 to 90% (with no condensation)	
Dimensions		(W x D x H): 475 x 313.4 x 319.2 mm (18.71" x 12.35" x 12.58")	(W x D x H): 475 x 313.4 x 274.2 mm (18.71" x 12.35" x 10.80")
Weight		21.2kg (standard)	20.2kg (standard)
Regulatory		FCC Class B, EN55022 Class B, UL (CUL), TUV	
<b>ACCESSORIES &amp; OPTIONS</b>			
Options		Cutter unit, Unwinder, Simple stacker, Memory expansion, Calendar ROM	

**Contact Us:** If you have further enquiries, please contact us for more information & discussion.

## Million Tech Development Limited



Address: Unit 509, 5/F, Tower II, Cheung Sha Wan Plaza, 833 Cheung Sha Wan Road, Kowloon, Hong Kong

General Line: (852) 2788 3306

F a x : (852) 2319 2967

Website: <https://milliontech.com>

Sales Enquiry: (852) 2784 2868

Email: [sales@milliontech.com](mailto:sales@milliontech.com)

Service Hotline: (852) 2784 2888

Email: [helpdesk@milliontech.com](mailto:helpdesk@milliontech.com)

**Contact** For more information about SATO around the globe, visit [www.satoworldwide.com](http://www.satoworldwide.com)

### AMERICAS

10350A Nations Ford Road Charlotte, NC 28273

Tel: (704) 644-1650

Fax: (704) 644-1662

E: [satosales@satoamerica.com](mailto:satosales@satoamerica.com)

For sales & general enquiries: [sales@satogbs.com](mailto:sales@satogbs.com)

### ASIA PACIFIC & OCEANIA

438B, Alexandra Road, #09-01/02, Alexandra Technopark

Singapore 119968

Tel: (65) 6271-5300

Fax: (65) 6273-6011

E: [sales@satoasiapacific.com](mailto:sales@satoasiapacific.com)

### EUROPE

Lambroekstraat 5A, 1831 Diegem, Belgium

Tel: (32) 2 719 03 90

Fax: (32) 2 719 03 99

E: [info@be.satoeurope.com](mailto:info@be.satoeurope.com)