



# Heavy-Duty Industrial Barcode Printer for the Most Demanding of Applications



## **M84PRO** Series

### INDUSTRY VERTICALS

- "Entry Level" Print & Apply Market
- Manufacturing
- Retail
- Supply Chain

### APPLICATIONS

- Bottle & Container Labelling
- Compliance Labelling
- Food Labelling
- Circuit Board Labelling
- Serial Plate Labelling
- Surgical Equipment Labelling
- Diagnostic Kit Labelling

*Heavy Duty Industrial Construction* ▶

*Powerful Memory* ▶

*Easy Connectivity* ▶

*Option of Increasing Print Resolution* ▶

*Allows Users to Switch Print Resolution  
Simply by Changing Printheads* ▶

*Windows™ Compatible* ▶



# General Specifications

M84PRO



PRINTER MODEL		M84Pro-2	M84Pro-3	M84Pro-6
<b>PRINTING SPECIFICATIONS</b>				
Print Method		Direct Thermal/Thermal Transfer		
Print Resolution		8 dots/mm (203dpi)	12 dots/mm (305dpi)	24 dots/mm (609dpi)
Max. Print Speed		254mm/sec (10ips)	203mm/sec (8ips)	152mm/sec (6ips)
Max. Print Width		104mm (4.1")		
Max. Print Length		1249mm (49.21")	835mm (32.9")	356mm (14.03")
<b>MEDIA SPECIFICATIONS</b>				
Sensor Type		Transmissive sensor for gap, Reflective sensor for I-mark		
Media		Roll Paper: Max External Diameter 218.4mm (8.6"), Face-in Paper core Internal Diameter 76.2mm (3") Fan Fold Paper: Max Folding Height 110mm (4.33")		
Media Type (Thickness)		0.08 to 0.26mm (0.003" to 0.010")		
Media Size	Continuous	Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 6 to 356mm (0.24" to 14.03"), inclusive backing paper size 9 to 359 mm (0.35" to 14.14")		
	Tear OFF	Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 16 to 356mm (0.63" to 14.03"), inclusive backing paper size 19 to 359 mm (0.75" to 14.14")		
	Cutter / Dispensing	Width: 22 to 125mm (0.87" to 4.93"), inclusive backing paper size 25 to 128 mm (0.99" to 5.04") Pitch: 30 to 356mm (1.18" to 14.03"), inclusive backing paper size 33 to 359 mm (1.30" to 14.14")		
<b>MEMORY PROCESSING</b>				
Memory		Flash memory 2MB. Expandable memory 4MB		
CPU		32 bit RISC		
<b>COMMUNICATION INTERFACES</b>				
Plug in Interface Cards		Serial - RS232C Parallel - IEEE1284 Ethernet - 10/100BaseT Wireless 802.11g RS422/485		
Others		USB External Connector Port		
<b>FONTS/BARCODE SYMBOLOGIES</b>				
Internal Fonts		XU 5x9 dots, XS 17x17 dots, XM 24x24 dots, XB 48x48 dots, XL 48x48 dots OCR-A 15x22 dots      OCR-A 22x33 dots      OCR-A 44x66 dots OCR-B 20x24 dots      OCR-B 30x36 dots      OCR-B 60x72 dots		
Internal Raster Fonts		CG Times, CG Triumvirate		
Barcodes	1D Barcode	UPC-A/E, EAN, JAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, Inter-leaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, NW-7, MSI, Postnet, Bookland		
	2D Barcode	QRCode, PDF 417, MaxiCode, Data Matrix		
	Character Rotation	0°, 90°, 180°, 270° rotation		
<b>OPERATING &amp; ENVIRONMENTAL</b>				
Power Consumption		AC 100 / 230V +/- 10% Peak 190VA 130W (Standby 24VA 16W)		
Environment		Operating Environment: 5 to 40°C / 30 to 80% (with no condensation) Storage Environment: -5 to 60°C / 30 to 90% (with no condensation)		
Dimensions		(W x D x H): 265 x 435 x 335 mm (10.44" x 17.14" x 13.12")		
Weight		18.5kg (standard)		
Regulatory		VCCI (Class B), FCC (Class B), UL, CUL, CE		
<b>ACCESSORIES &amp; OPTIONS</b>				
Options		Cutter unit, Dispensing unit, Rewinder		

**Contact** For more information about SATO around the globe, visit [www.satoworldwide.com](http://www.satoworldwide.com)

**AMERICAS**

10350A Nations Ford Road Charlotte, NC 28273  
Tel: (704) 644-1650  
Fax: (704) 644-1662  
E: [satosales@satoamerica.com](mailto:satosales@satoamerica.com)

**ASIA PACIFIC & OCEANIA**

438B, Alexandra Road, #09-01/02, Alexandra Technopark Singapore 119968  
Tel: (65) 6271-5300  
Fax: (65) 6273-6011  
E: [sales@satoasiapacific.com](mailto:sales@satoasiapacific.com)

**EUROPE**

Lambroekstraat 5A, 1831 Diegem, Belgium  
Tel: (32) 2 719 03 90  
Fax: (32) 2 719 03 99  
E: [info@be.satoeurope.com](mailto:info@be.satoeurope.com)



Unit 509, 5/F, Tower II, Cheung Sha Wan Plaza, 833 Cheung Sha Wan Road, Kowloon, Hong Kong  
Tel: (852) 2784 2868/ (852) 2788 3066 Fax: (852) 2319 2967  
Email: [sales@milliontech.com](mailto:sales@milliontech.com)  
Website: [www.milliontech.com](http://www.milliontech.com)

*We Create [Value]<sup>2</sup>*