

Communication and Charging cradle for

Denso BHT-300 / BHT-800 / BHT-1200 / BHT-1100 / BHT-1300 with extra features



MT-CU-320

CU-301/321 Compatible
for BHT-300



MT-CU-820

CU-821 Compatible for BHT-800

MT-CU-1311

CU-1321 Compatible for BHT-1300



MT-CU-1000

USB Interface for Denso BHT-1200

MT-CU-1011

USB Interface for Denso BHT-1100



Additional Features

- ✓ Powerless connection with Denso BHT-320 / BHT-800 / BHT-1200 / BHT-1100 / BHT-1311
- no power adapter is needed for communication
- ✓ Ultra slim and exquisite streamline enclosure
- ✓ External Battery Charger option for BHT-1200 & BHT-1100 Battery (MT-CU-1000 & MT-CU-1011 only)

Contact Us: If you have further enquiries, please contact us for more information & discussion.

Million Tech Development Limited

Address: Unit 509, 5/F, Tower II, Cheung Sha Wan Plaza, 833 Cheung Sha Wan Road, Kowloon, Hong Kong

General Line: (852) 2788 3306

Sales Enquiry: (852) 2784 2868

Service Hotline: (852) 2784 2888

F a x : (852) 2319 2967

Email: sales@milliontech.com

Email: helpdesk@milliontech.com

Website: <https://milliontech.com>

Communication and Charging cradle for Denso BHT-300 / BHT-800 / BHT-1200 / BHT-1100 / BHT-1300 with extra features



Communication Cradle
(Bundle USB cable)

MT-CU-320
Compatible CU-301/321



Communication Cradle
(Bundle USB cable)

MT-CU-1000 / MT-CU-1011
USB Interface for Denso BHT-1200 / BHT-1100



Communication Cradle
(Bundle USB cable)

MT-CU-820
Compatible CU-821
MT-CU-1311
Compatible CU-1321



Optional Battery Charger
(for MT-CU-1000)

MT-CU-1000-EC



Communication Cradle with Optional Charger
(Bundle USB cable)

MT-CU-1000 / MT-CU-1000-EC
MT-CU-1011 / MT-CU-1000-EC

Power Adapter Options



AC/DC Wall Mount Power Adapter 12VDC/2000mA (UK type)

ADA-SAW24-12-2000-W



AC/DC Desktop Power Adapter 12VDC/2000mA
(for overseas countries)

ADA-SAW24-12-2000-D

Specifications

	MT-CU-1000 / MT-CU-1011	MT-CU-1000-EC	MT-CU-1000/MT-CU-1000-EC MT-CU-1011/MT-CU-1000-EC	MT-CU-320	MT-CU-820	MT-CU-1311
Dimensions and Weight						
Dimension (mm)	90(L) x 100(W) x 85(H)	70(L) x 73(W) x 46(H)	130(L) x 100(W) x 85(H)	110(L) x 115(W) x 90(H)	110(L) x 115(W) x 80(H)	
Weight (g)	150	60	210	250		
Interface						
USB Client Port	Maximum 12Mbps					
USB Com / RS232				115200bps		
Environment						
Operation Temp.	0°C to +40°C					
Storage Temp.	-20°C to +60°C					
Humidity	10% -90% RH (no condensation)					
Electrical Characteristic						
Operation Voltage	DC 12V					
Current Consumption	Max. 800mA	Max. 550mA	Max. 1350mA	Max. 1100mA	Max. 750mA	Max. 800mA
System Compatibility						
ActiveSync	Windows 2000 / XP					
Mobile Device Center	Windows Vista / 7					
BHT IR				Yes		
Y modem				Yes		

Contact Us: if you have further enquiries, please contact us for more information & discussion.

Million Tech Development Limited

Address: Unit 509, 5/F, Tower II, Cheung Sha Wan Plaza, 833 Cheung Sha Wan Road, Kowloon, Hong Kong

General Line: (852) 2788 3306

Sales Enquiry: (852) 2784 2868

Service Hotline: (852) 2784 2888

F a x : (852) 2319 2967

Email: sales@milliontech.com

Email: helpdesk@milliontech.com

Website: <https://milliontech.com>